

Couplings



DN mm	DN inches	Range	Weight kg
50	2	43-64	6,4
65	2,5	63-84	7,8
80	3	85-107	9,5
100	4	107-134	13
125	5	132-160	14,5
150	6	159-192	20,7
175	7	192-227	22,4
200	8	218-252	25,4
250	10	266-300	31,8
300	12	315-350	36,7

Flange Adaptors



DN mm	DN inches	Range FA	Weight Kg
50	2	43-64	4,4
65	2,5	63-84	5,5
80	3	85-107	7,4
100	4	107-134	10,8
125	5	132-160	11,6
150	6	159-192	17,8
175*	7	192-227	24,3
200	8	218-252	26,3
250	10	266-300	31,4
300	12	315-350	38,5

* Flange size DN 200

Sleeve length for couplings is 200 mm

Material:

High quality ductile iron GGG 450-10

Coating:

High Quality epoxy, providing a long term corrosion protection along with resistance to abrasion and impact. *Other coatings are available on request*

Bolts and nuts:

High grade Steel 8.8 fasteners, coated with Dacromet™ Grade B 500. Dacromet™ coating is based on zinc and aluminium flakes that are passivated throughout the entire layer providing excellent anti-corrosion characteristics.

Stainless steel bolts and nuts are available on request

Rubber gaskets:

EPDM Grade E / WA as per BS EN 681-1:1996. *NBR Rubber is available on request.*

Features:

- Working pressures up to 16 bars
- Angular deflection 6° for couplings
- DIN, BS and ANSI in one flange design

ODS

Multi-line O.G. multi metal distributor



Couplings



DN mm	DN inches	Range	Weight kg
50	2	59-73	3,8
65	2,5	72-85	4,3
80	3	88-103	4,5
100	4	108-128	5,6
125	5	132-146	6,8
125	5	139-153	6,9
150	6	159-182	8,5
175	7	192-209	9,2
200	8	218-235	9,8
225	9	250-267	12,3
250	10	271-289	14,3
300	12	322-340	16,2

Flange Adaptors



DN mm	DN inches	Range	Weight kg
50	2	59-73	3,6
65	2,5	72-85	4,3
80	3	88-103	4,8
100	4	108-128	5,1
125	5	132-146	6,7
125	5	139-153	6,8
150	6	159-182	8,0
175	7	192-209	8,9
200	8	218-235	9,5
225	9	250-267	11,4
250	10	271-289	14,4
300	12	322-340	18,0

Material:

High quality ductile iron GGG 450-10

Coating:

Epoxy coating, providing a long term corrosion protection along with resistance to abrasion and impact. *Other coatings are available on request*

Bolts and nuts:

High grade Steel 8.8 fasteners, coated with Dacromet™ Grade B 500. Dacromet™ coating is based on zinc and aluminium flakes that are passivated throughout the entire layer providing excellent anti-corrosion characteristics.

Stainless steel bolts and nuts are available on request

Rubber gaskets:

EPDM Grade E / WA as per BS EN 681-1:1996. *NBR gaskets are available on request.*

Features:

- Working pressures up to 16 bars
- Angular deflection 6° for couplings
- DIN, BS and ANSI in one flange design

ODS

Blackwell Ltd multi metal distributor

